

# 16GK6

## Power Pentode

### 9-PIN MINIATURE TYPE

*The 16GK6 is the same as the 6GK6 except for the following items:*

#### Heater Characteristics and Ratings:

Current. . . . .	0.300 ± 0.020	amp
Voltage (AC or DC) at heater amperes = 0.300 . . . . .	16.0	volts
Warm-up time (Average) . . . . .	11	sec

# 17AX3

## Half-Wave Vacuum Rectifier

### DUODECAR TYPE

*The 17AX3 is the same as the 6AX3 except for the following items:*

#### Heater Characteristics and Ratings:

Current. . . . .	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450 . . . . .	16.8	volts
Warm-up time (Average) . . . . .	11	sec

# 17AX4GTA

## Half-Wave Vacuum Rectifier

### For TV Damper Service

*The 17AX4GTA is the same as the 6AX4GTB except for the following items:*

#### Heater Characteristics and Ratings:

Current. . . . .	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450 . . . . .	16.8	volts
Warm-up time (Average) . . . . .	11	sec



# 17AY3, 17AY3A

## Half-Wave Vacuum Rectifier

NOVAR TYPE

For TV Damper Service

*The 17AY3 and 17AY3A are the same as the 6AY3 and 6AY3B, respectively, except for the following items:*

Heater Characteristics and Ratings:

Current. . . . .	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450 . . . . .	16.8	volts
Warm-up time (Average) . . . . .	11	sec

# 17BE3

## Half-Wave Vacuum Rectifier

DUODECAR TYPE

*The 17BE3 is the same as the 6BE3 except for the following items:*

Heater Characteristics and Ratings:

Current. . . . .	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450 . . . . .	16.8	volts
Warm-up time (Average) . . . . .	11	sec

# 17BF11

## Beam Power Tube— Sharp-Cutoff Pentode

DUODECAR TYPE

*The 17BF11 is the same as the 6BF11 except for the following items:*

Heater Characteristics and Ratings:

Current. . . . .	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450 . . . . .	16.8	volts
Warm-up time (Average) . . . . .	11	sec

