

**TUNG-SOL**

**TWIN-TRIODE AMPLIFIER**

**PHYSICAL SPECIFICATIONS**

EMITTER UNIPOTENTIAL CATHODE		PIN CONNECTIONS	
BASE	INTERMEDIATE SHELL OCTAL 8-PIN	PIN 1	GRID (T <sub>2</sub> )
CAP	NONE	PIN 2	PLATE (T <sub>2</sub> )
BULB	T-9	PIN 3	CATHODE (T <sub>2</sub> )
MAXIMUM DIAMETER	1 5/16"	PIN 4	GRID (T <sub>1</sub> )
MAXIMUM OVERALL LENGTH	3 5/16"	PIN 5	PLATE (T <sub>1</sub> )
MAXIMUM SEATED HEIGHT	2 3/4"	PIN 6	CATHODE (T <sub>1</sub> )
		PIN 7	HEATER
		PIN 8	HEATER
			TOP CAP NONE

**RATINGS**  
AMPLIFIER - EACH UNIT

HEATER OR FILAMENT VOLTAGE (AC OR DC)	12.6	VOLTS
HEATER OR FILAMENT CURRENT	0.15	AMPS.
MAXIMUM PLATE VOLTAGE	250	VOLTS
MAXIMUM GRID VOLTAGE	0	VOLTS
MAXIMUM PLATE DISSIPATION	.1	WATTS
MAXIMUM SCREEN DISSIPATION		WATTS

RATINGS ARE TO BE INTERPRETED ACCORDING TO RMA STANDARD m8-210

**CAPACITANCES**  
TRIODE UNIT T<sub>1</sub>                      TRIODE UNIT T<sub>2</sub>

GRID TO CATHODE	3.0	3.4	μuf
PLATE TO CATHODE	3.8	3.2	μuf
GRID TO PLATE	2.8	2.8	μuf
PLATE TO PLATE	0.4		μuf
GRID TO GRID	0.65		μuf
GRID T <sub>2</sub> TO PLATE T <sub>1</sub>	0.13		μuf

**TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS**  
**CLASS A<sub>1</sub> AMPLIFIER**

HEATER OR FILAMENT VOLTAGE (AC OR DC)	12.6	VOLTS
HEATER OR FILAMENT CURRENT	0.15	AMPS.
PLATE VOLTAGE	250	VOLTS
GRID VOLTAGE	-2	VOLTS
CONTROL GRID VOLTAGE		VOLTS
PEAK AF SIGNAL VOLTAGE		VOLTS
ZERO-SIGNAL PLATE CURRENT	2.3	MA.
ZERO-SIGNAL SCREEN CURRENT		MA.
MAXIMUM-SIGNAL PLATE CURRENT		MA.
MAXIMUM-SIGNAL SCREEN CURRENT		MA.
PLATE RESISTANCE (APPROX.)	44000	OHMS
TRANSCONDUCTANCE	1600	μMHOS
AMPLIFICATION FACTOR	70	
LOAD RESISTANCE		OHMS
TOTAL HARMONIC DISTORTION		PER CENT
POWER OUTPUT		WATTS
CONTROL GRID VOLTAGE FOR TRANSCONDUCTANCE	μMHOS	VOLTS

PRINTED IN U. S. A.

PLATE  
1318-1  
SEPT. 23  
1943