



Excellence in Electronics

The type 12ABP — is a 12-inch electrostatic focus and magnetic deflection cathode-ray tube suitable for radar applications. A low-voltage electrostatic focus lens is employed, designed to operate at or near cathode potential to afford substantially automatic focus, independent of accelerator voltage variations. In addition, the 12ABP — employs a high resolution electron gun.

The final A designates a metallized screen for greater light output, improved contrast, and minimizing screen charging effects.

MECHANICAL DATA

BASE: Small Shell Duodecal 6--Pin

CAP: Recessed Small Cavity

TERMINAL CONNECTIONS:

- | | |
|----------------|---------------------|
| Pin 1 Heater | Pin 11 Cathode |
| Pin 2 Grid #1 | Pin 12 Heater |
| Pin 6 Grid #4 | Cap Grids #3 and #5 |
| Pin 10 Grid #2 | (Collector) |

MOUNTING POSITION: Any

GENERAL DATA

	<u>12ABP7</u>	<u>12ABP14</u>	<u>12ABP19A</u>
	<u>12ABP7A</u>	<u>12ABP14A</u>	
Phosphor	#7	#14	#19
Fluorescence	Blue	Blue	Orange
Phosphorescence	Yellow	Orange	Orange
Persistence	Long	Medium - Long	Long
Focusing Method	Electrostatic	Electrostatic	Electrostatic
Deflecting Method	Magnetic	Magnetic	Magnetic
Deflection Angle	55°	55°	55°

ELECTRICAL DATA

HEATER CHARACTERISTICS:

Heater Voltage	6.3 volts
Heater Current	0.6 ± 10% amps.
Peak Heater - Cathode Voltage: (Max.)	
Heater Negative with Respect to Cathode	180 volts DC
Heater Positive with Respect to Cathode	180 volts DC

DIRECT INTERELECTRODE CAPACITANCES: (μfds.) (approx.)

Grid #1 to all other electrodes	6
Cathode to all other electrodes	5

DESIGN CENTER MAXIMUM RATINGS:

Collector Voltage ▲	12,000 volts DC
Grid #4 Voltage (Focusing Electrode)	-500 to +1000 volts DC
Grid #2 Voltage	700 volts DC
Grid #1 Voltage:	
Negative - Bias Value	180 volts DC
Positive - Bias Value *	0 volts DC
Positive - Peak Value	0 volts DC


CHARACTERISTICS AND TYPICAL OPERATION:

Collector Voltage ▲	10,000 volts DC
Grid #4 Voltage (Focusing Electrode) ●	0 to 300 volts DC
Grid #2 Voltage	300 volts DC
Grid #1 Voltage ⊕	-28 to -72 volts DC
Line Width ■	0.019 inch max.
Spot Position (undeflected) □	5/8 inch

MAXIMUM CIRCUIT VALUES:

Grid #1 Circuit Resistance	1.5 max. megohms
----------------------------	------------------

TYPE
12ABP7
12ABP7A
12ABP14
12ABP14A
12ABP19A



BOTTOM VIEW

12M.

Tentative Data

RAYTHEON MANUFACTURING COMPANY

RECEIVING TUBE AND SEMICONDUCTOR OPERATIONS

TYPE

12ABP7 - 12ABP7A
12ABP14 - 12ABP14A
12ABP19A



CATHODE RAY TUBE

- * *At or near this rating, the effective resistance of the collector supply should be adequate to limit the collector input power to 6 watts.*
- ▲ *Brilliance and definition decrease with decreasing collector voltages. In general, collector voltage should not be less than 8000 volts.*
- ◆ *Cathode should be returned to one side or to the mid-tap of the heater transformer winding.*
- *With grid #1 voltage adjusted to produce a collector current of 100 μ A, with the pattern adjusted for best overall focus. Measured with a 525-line interlaced and synchronized 7 1/2 X 10 inch pattern, with interlaced line blanking (current measured before applying blanking.)*
- ⊕ *Visual extinction of 7 1/2 X 10 inch raster pattern.*
- *Measured with a 525-line interlaced and synchronized pattern with interlaced line blanking. Pattern width adjusted to 90% of minimum useful screen diameter. I_b - 100 μ A, measured before applying blanking. Line width is the merged raster height of divided by the number of lines (262.5) (measured in center of tube face). To avoid damage to the screen of the 12ABP19A, it is recommended that the screen current be not more than 50 μ A. when measuring line width. The line width under these conditions will be 0.019 inch maximum (current measured before applying blanking) for P7 and P14 phosphors, and 0.018 inch for the P19A*
- *The center of the undeflected, focused spot will fall within a circle of 5/8 inch radius concentric with the center of the tube face, with tube shielded.*

RAYTHEON MANUFACTURING COMPANY

RECEIVING TUBE AND SEMICONDUCTOR OPERATIONS



TYPE
 12ABP7 - 12ABP7A
 12ABP14- 12ABP14A
 12ABP19A

CATHODE RAY TUBE

